

Inverters Designed For Beauty

DNS Series

Dual-MPPT, Single-Phase

- Start-up voltage at 120V
- Wide range of MPPT voltage
- Small, lightweight and easy to install
- Built-in anti-reverse function
- Fanless and noiseless



GoodWe DNS series is a perfect match for residential installations thanks to its compact size and light weight. Manufactured for durability and longevity under modern industrial standards, GoodWe DNS series is IP65 rated so it can be mounted either inside or outside your home. With a low start-up voltage of only 120V and the widest MPPT voltage range of 80-550V, these inverters can provide greater options for your household system. The GoodWe DNS series is also extremely light, 30% lighter than other inverters.

Technical Data	GW3000D-NS	GW3600D-NS	GW4200D-NS	GW5000D-NS	GW6000D-NS
----------------	------------	------------	------------	------------	------------

PV String Input Data

Max. DC Input Power (W)	3900	4680	5460	6500	7200
Max. DC Input Voltage (V)	600	600	600	600	600
MPPT Range (V)	80~550	80~550	80~550	80~550	80~550
Start-up Voltage (V)	120	120	120	120	120
Nominal DC Input Voltage (V)	360	360	360	360	360
Max. Input Current (A)	11/11	11/11	11/11	11/11	11/11
Max. Short Current (A)	13.8/13.8	13.8/13.8	13.8/13.8	13.8/13.8	13.8/13.8
No. of MPP Trackers	2	2	2	2	2
No. of Input Strings per Tracker	1	1	1	1	1

AC Output Data

Nominal Output Power (W)	3000*1	3680*1	4200*1	5000*1	6000*1
Max. Output Apparent Power (VA)	3000	3680	4200	5000	6000
Nominal Output Voltage (V)	220/230	220/230	220/230	220/230	220/230
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	13.6	16	19	22.8	27.3
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)				
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%

Efficiency

Max. Efficiency	97.8%	97.8%	97.8%	97.8%	97.8%
European Efficiency	97.5%	97.5%	97.5%	97.5%	97.5%

Protection

Anti-Islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated

General Data

Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Convection				
Noise (dB)	<25	<25	<25	<25	<25
User Interface	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED
Communication	RS485 or WiFi or LAN	RS485 or WiFi or LAN	RS485 or WiFi or LAN	RS485 or WiFi or LAN	RS485 or WiFi or LAN
Weight (kg)	13	13	13	13	13.5
Size (Width*Height*Depth mm)	354*433*147	354*433*147	354*433*147	354*433*147	354*433*147
Protection Degree	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1
Topology	Transformerless				

Certifications & Standards

Grid Regulation	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G83, IEC61727, IEC62116, CEI 0-21, RD 1699:2011, UNE 206006 IN: 2011, UNE 206007-1 IN: 2013	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G59, IEC61727, IEC62116, CEI 0-21, RD 1699:2011, UNE 206006 IN: 2011, UNE 206007-1 IN: 2013	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G59, IEC61727, MEA, PEA, IEC62116, CEI 0-21, RD 1699:2011, UNE 206006 IN: 2011, UNE 206007-1 IN: 2013	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G59, IEC61727, MEA, PEA, IEC62116, CEI 0-21
Safety Regulation	IEC62109-1&-2			
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, EN61000-4-16, EN61000-4-18, EN61000-4-29			

*1: For CEI 0-21 Nominal Output Power GW3000D-NS is 2700, GW3680D-NS is 3350, GW4200D-NS is 3800, GW5000D-NS is 4540, GW6000D-NS is 5450. For AS4777, Nominal Output Power GW5000D-NS is 4999.

Color Options