

Features:









- » A stylish black and dark grey finish.
- » LED Work Light, High Power White Light, suitable for outdoor lighting and emergency rescue. It has 3 modes, Lighting, Strobe and SOS.
- » 1 x DC (5521 port) Input Port (10-28V): With original wall charger (19V/6.32A), Car Charging (12V), also could be recharged by Solar Panel* (18V).
- » 4 x DC (5521 port) Output Port, 1 x Cigarette Lighter Output Port. (Total 12V/8A, 10A Max).
- » 2 x USB-A Output (5V/2.4A), 1 x USB-A Fast Charge Output QC18W (5V/9V/12V), 1 x USB-C (USB-C) Input / Output PD 100W, 1 x USB-C (USB-C) Output PD 60W.
- » 4* AC (US/JP) or 2 AC (EU/AU/CN) Output Port, 110V/60Hz or 220V/50Hz, Rated Power 1000W (Pure Sine Wave)
- » Industrial 1000W pure sine wave bidirectional inverter technology.
- » Excellent ventilation and Noiseless Design, offers industryleading conversion efficiency.
- » 9 Multiple protection systems: Short Circuit, Over Current, Over Voltage, Over-heat, Low Voltage Protections

Applications:

- » Mobile Office: supply power for Mobiles, Tablets, Laptops, Printers, Cameras, Lighting, etc.
- » Outdoor Activities: power for Drones, E- bikes, mini refrigerator electronic musical instruments, etc.
- » Home Use: Lighting, Electric Fans, Television and other appliances with Power Consumption under 1000W.
- » Car Use: Car Refrigerator, Vacuum Cleaner, Air Purifier, and products Power Consumption under 1000W.
- » Medical Use: Heart Pacemaker, Ventilator, Oxygenator, Electric Wheelchair, Blood Pressure Monitor, Blood Glucose Meter, Emergenc Equipment with Power Consumption under 1000W.

^{*} Solar panel not included and need purchasing separately.



1000W Portable Power Station



Medical Equipment



Battery Capacity 716.8Wh Lithium Ion Battery, 22.2V/32Ah **USB** Output USB-A1&2 Output 5V / 2.4A USB-A3 QC18W, Support 5V3A/9V2A/12V1.5A USB-C1 Input/Output PD 100W etc. USB-C2 PD 60W, support PD, QC, FCP, Apple, AFC DC Output (Over 12V Cigarette Lighter Port 12V/10A Regulated Current Protection, 4 xDC Output (5521 Port) 12V/Max 10A Total 10A) DC Input Adapter Charging Input: 10V~28V Max 10A, MPPT Built-in (5521 Port) Solar Panel* Charging (18V) Cigarette Lighter Charging (12V) 1. NO DIRECT SUNLIGHT 2. DON'T PUT IN ENVIRONMENTS ABOVE 60°C AC110V 60Hz or 220V 50Hz, 500W Max AC Input AC Input Voltage AC Output Voltage 1* AC Output 110V/60Hz or 220V/50Hz, Rated AC Output Power 1000W, Peak Power 2000W Dual LED Light LED Work Light 5W, 3 modes: Lighting/ Strobe/ SOS Temperature -10°C to 45°C (Best: 20°C to 30°C) Discharging Temperature Storage Temperature -10°C to 45°C (Best: 20°C to 30°C) **Charging Temperature** 0°C to 45°C Dimension (W*H*L): 295*190*270mm 1 inner boxes in an outer box Materials Housing: ABS+PC/VO Flame Retardant Material Carton Size: 37×26×46cm Product Net Weight: About 10Kg GW/Carton: 12.5KG Accessories AC Adaptor x 1 pc 48 pcs in a pallet(120x100cm) Car Charger x 1 pc (optional) Pallet Size: 120x100x199cm USB-A to USB-C Charging Cable x 1 pc (optional) GW/Pallet: 600KG User Manual (OEM) 384 pcs in a 20ft container Package (OEM) 816 pcs in a 40ft container

Power the Most of Appliances

Pure Sine Wave









Laptop

Cooker





Phone Camera

Drone

Car Refrigerator

Outdoor Party



Outdoor Work



Camping





^{*} Solar panel not included and need purchasing separately.